

APC Back-UPS Pro, 1350VA/ 810W, Tower, 120V, 10x NEMA 5-15R outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

BR1350MS

Product availability: Stock - Normally stocked in distribution facility

#### **Overview**

Lead time	Usually in Stock
Main	
Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	810 W
Rated power in VA	1350 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
output connection type	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Number of cables	1
Battery Type	Lead-Acid battery

### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	2
Battery Charge Power (Watts)	10 W rated
Battery Life	35 year(s)
Replacement battery	APCRBC161 ☐
Extendable Run Time	0

#### **General**

Provided equipment	Coaxial cable User Manual USB cable	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

product web sub-family	Gaming performance
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

# **Physical**

Height	10.2 in (26 cm)
Width	3.9 in (10 cm)
Depth	14.5 in (36.8 cm)
Net Weight	25.8 lb(US) (11.7 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input Frequency	60 Hz +/- 3 Hz
Efficiency at full load	88147 V
Maximum Input Current per Phase	12 A
Switching current capacity	15 A

# Output

Max Configurable Power (Watts)	810 W
Output Frequency (sync to mains)	60 Hz +/- 3 Hz sync to mains
Topology	Line Interactive
Waveform Type	Sine wave
Maximum configurable power in VA	1350 VA
Transfer Time	8ms typical : 10 ms maximum

# Conformance

Product Certifications	ENERGY STAR V2.0 (USA) NOM TUV C-US certified
Equipment protection policy	Lifetime : \$500000

### **Environmental**

Ambient Air Temperature for Operation	32.0000000000104.0000000000 °F (040 °C)
Relative Humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient Air Temperature for Storage	5.0000000000104.00000000000 °F (-1540 °C)
Storage Relative Humidity	095 % non-condensing
Storage altitude	010000 ft (0.00000000003048.0000000000 m)

acoustic level 45 dBA

### **Communications & Management**

Control panel Multi-function LCD status and control console

## **Surge Protection and Filtering**

Surge energy rating	1080 J
Filtering	Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping
	response time: in

### Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	00731304335399
Returnability	No
Country of origin	PH

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.12 in (35.87 cm)
Package 1 Width	19.0 in (48.2 cm)
Package 1 Length	8.8 in (22.3 cm)
Package 1 Weight	29.3 lb(US) (13.3 kg)
SCC14	10731304335396

### **Contractual warranty**

Warranty 3 years repair or replace

## Sustainability Screen Premium

**Green Premium** TM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

### Resource performance

**Energy Efficient Product** 



Take-Back Program Available

#### Well-being performance

Mercury Free



Rohs Exemption Information

Yes

#### **Environmental Certifications**



Energy Star®

ENERGY STAR UPS V2.0 (USA)

#### **Certifications & Standards**

**Reach Regulation REACh Declaration Eu Rohs Directive** Compliant with Exemptions **Environmental Disclosure Product Environmental Profile Circularity Profile** End of Life Information California Proposition 65 "WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"

Oct 2, 2024

Image of product / Alternate images

#### **Alternative**





Image of product in real life situation



